

A

B

C

D

E

F

REV	DESCRIPTION	DESIGN	DATE
A	NEW RELEASE	Lingqing	2020/12/25

1

2

3

4

5

1




2

3





4

5

SCALE:1/2



LAST CIRCUIT

FIRST CIRCUIT
IDENTIFIER SYMBOL**Specifications:**Contact resistance: $\leq 10\text{m}\Omega$ Insulation resistance: $\geq 1000\text{M}\Omega$

Rated voltage: 250V AC DC

Rated current: 5.0A AC DC

Withstand Voltage: 1000V AC/minute

Temperature Range: $-25^{\circ}\text{C} \sim +85^{\circ}\text{C}$

Housing: PA66 UL94V-0, BLACK

ORDER INFORMATION:

A3001Y-2**-A7K-P		
PART No.		PACKAGING: P=PE
No.OF CIRCUITS:		
201~212		
PLASTIC MATERIAL:		
A76K=PA66(BLACK)		

JKUN 温州健坤接插件有限公司
WENZHOU JKUN CONNECTOR CO.,LTD.

TITLE:
3.0mm PITCH Housing

GENERAL TOLERANCE		USE:	PART NO.:
X. ± 0.50	X. $\pm 5^{\circ}$	CUSTOMER	
X.X ± 0.30	X.X $\pm 2^{\circ}$	APPD: WangFeng	DWG NO.:
X.XX ± 0.20	X.XX $\pm 1^{\circ}$	CHKD: Shaojinghe	JKUN-GCKH-0676
UNITS: mm		DR: Zenglingqing	SCALE 1 : 1
			SHEET 1 / 1